

## LED Area Lights Series

### MLAR



MLAR70LED50



MLAR100LED50



MLAR140LED50



### PRODUCT DESCRIPTION:

MaxLite's LED Area Lights are efficient, energy saving replacements for metal halide and high-pressure sodium fixtures, containing an universal voltage driver.

The fixtures come standard with a 6" extruded arm in standard dark bronze; a white finish is also available.

### FEATURES:

- Replaces up to 400 Watt pulse start metal halide
- CCT: 5000K
- CRI > 66
- Universal 100 to 277V, 50/60 Hz driver
- 6" extruded aluminum arm included
- Full cutoff classification both type V square and wide distributions
- Black ceramic paint frit lens mask reduces glare and improves appearance
- Constructed without any hazardous materials
- Compatible with mechanical relay type Photocell and occupancy sensor
- LM-79/80 reports available
- Calculated L<sub>70</sub> based on LM-80 testing > 100,000 hours
- Five year limited warranty

#### MODEL SELECTION (Full list of order codes on pg. 3)

Typical order example: MLAR140LED50WPCMS4

MLAR		LED	50				
FAMILY	WATTAGE	TECH.	(CTT)	COLOR	VOLTAGE	PHOTOCONTROL	CONTROL
MLAR= Large Flood	70= 70W 100= 100W 140= 145W	LED= LED	50= 5,000K	OMIT= Bronze (Standard) W= White <sup>1</sup>	OMIT= 120-277V UH= 347-480V	OMIT= None PC= Rotatable Photocontrol Socket	OMIT= None MS4= Motion/Daylight Sensor (Hi/Low/Off)

#### REPLACEMENT / OPTIONAL ARMS / ACCESSORIES

ORDER CODE	MODEL NUMBER	DESCRIPTION	ACCESSORIES IMAGES
71454	AR6STBZ	6" area light arm for 4"-6" square poles (Bronze)	
71455	AR12STBZ	12" area light arm for 4"-6" square poles (Bronze)	
71453	AR12RPBZ	12" area light arm for 4" round poles (Bronze)	
72710	MLARFLGS	Glare/House Side Shield	

#### NOTES:

- <sup>1</sup> Consult factory for lead time

**SPECIFICATIONS:**

MLAR70LED50 MLAR100LED50 MLAR140LED50 MLAR70LED50/5W MLAR100LED50/5W MLAR140LED50/5W

ITEM	SPECIFICATION	TYPE V SQUARE OPTICS - DETAILS			TYPE V SQUARE WIDE OPTICS - DETAILS		
GENERAL PERFORMANCE	Spacing Criteria	Available upon request					
	Power Consumption	62W	100W	136W	62W	100W	136W
	Lumens Delivered	5,220	9,130	11,730	5,470	9,160	12,140
	Efficacy	85 lm/w	92 lm/w	86 lm/w	89 lm/w	92 lm/w	90 lm/w
	CRI	68			70		68
	Beam Angle	74°	78°	79°	117°	115°	116°
	Field Angle	94°		93°	151°	153°	151°
	Color Temperature (CCT)	5000K					
	CRI	68 min					
	Lumen Maintenance (L70)	100,000 hours					
ELECTRICAL	Power Factor	Over 90%					
	Input Voltage	120V-277V 50/60 Hz					
PHYSICAL	Dimension	16.5" x 16.5" x 7.5"					
	EPA	1.10					
	Weight	17 lbs.					
	Housing	Aluminum					
	Lens	Tempered glass					
	Mounting	6" Ext. Alum Arm, Std					
	Operating Temperature	-30°F to 115°F					
CERTIFICATION	Certification	cETLus, FCC, LM79, LM80, DLC					
	Material Usage	RoHS compliant; no mercury					
	Environment	Outdoor					
	Humidity	20% - 85%, RH, non condensing					
	Warranty	5 Year					

Lighting layouts and spacing criteria available upon request

**DIMENSIONS:**



**OPEN OPTICS OPTIONS:**



**CONSTRUCTION:**

**Fixture:** The heavy duty cast aluminum one-piece housing is polyester powder coated and sealed from dirt, water and insects with a hinged door with a shock-proof tempered glass.

**Lens:** Tempered Glass

**LED Module:** Copper plating provides high thermal transfer rate, minimizing the junction temperature of the LEDs.

**Finish:** Dark bronze; white optional (consult factory for lead times)

**CONTROL:**

- 7 time delay settings
- 3 Daylight Harvesting setting
- Omni-directional quad element infrared sensor
- 0-10V selectable output for low dim control
- Walk test and sensor operation LED indicator
- Direct lead wires for easy wiring connections
- 8 rotary DIP switch selectable control modes
- 7 low dim levels changeable via Accu-Set
- 3 selectable ambient Light Level thresholds

**ORDERING:**

ORDER CODE	MODEL	DESCRIPTION
71324	MLAR70LED50	AREA LIGHT 70W LED 5000K WITH 6 ARM
72026	MLAR70LED50/5W	AREA LIGHT 70W LED 5000K TYPE V WIDE WITH 6 ARM
73054	MLAR70LED50PC	AREA LIGHT 70W LED 5000K WITH 6 ARM WITH ROTATABLE PHOTOCONTROL RECEPTACLE
73055	MLAR70LED50PC/5W	AREA LIGHT 70W LED 5000K TYPE V WIDE WITH 6 ARM WITH ROTATABLE PHOTOCONTROL RECEPTACLE
71641	MLAR70LED50W	AREA LIGHT 70W LED 5000K WHITE WITH 6 ARM
72931	MLAR70LED50W/5W	AREA LIGHT 70W LED 5000K TYPE V WIDE WITH 6 ARM WHITE
73467	MLAR70LED50WUH/5W	AREA LIGHT 70W LED 5000K TYPE V WIDE WITH 6 ARM WHITE, 347/480V
71325	MLAR100LED50	AREA LIGHT 100W FLOOD LED 5000K WITH 6 ARM
72028	MLAR100LED50/5W	AREA LIGHT 100W LED 5000K TYPE V WIDE WITH 6 ARM
72596	MLAR100LED50PC	AREA LIGHT 100W LED 5000K WITH 6 ARM WITH ROTATABLE PHOTOCONTROL RECEPTACLE
72597	MLAR100LED50PC/5W	AREA LIGHT 100W LED 5000K TYPE V WIDE WITH 6 ARM WITH ROTATABLE PHOTOCONTROL RECEPTACLE
73109	MLAR100LED50UH	AREA LIGHT 100W LED 5000K WITH 6 ARM, 347/480V
71642	MLAR100LED50W	AREA LIGHT 100W LED 5000K WHITE WITH 6 ARM
72029	MLAR100LED50W/5W	AREA LIGHT 100W LED 5000K WHITE TYPE V WIDE WITH 6 ARM
71326	MLAR140LED50	AREA LIGHT 140W LED 5000K WITH 6 ARM
72030	MLAR140LED50/5W	AREA LIGHT 140W LED 5000K TYPE V WIDE WITH 6 ARM
72599	MLAR140LED50PC	AREA LIGHT 140W LED 5000K WITH 6 ARM WITH ROTATABLE PHOTOCONTROL RECEPTACLE
72982	MLAR140LED50PC/5W	AREA LIGHT 140W LED 5000K TYPE V WIDE WITH 6 ARM WITH ROTATABLE PHOTOCONTROL RECEPTACLE
73694	MLAR140LED50UH	AREA LIGHT 140W LED 5000K TYPE V WITH 6 ARM, 347/480V
72946	MLAR140LED50UH/5W	AREA LIGHT 140W LED 5000K WHITE TYPE V WIDE WITH 6 ARM, 347/480V
71643	MLAR140LED50W	AREA LIGHT 140W LED 5000K WHITE WITH 6 ARM
72031	MLAR140LED50W/5W	AREA LIGHT 140W LED 5000K WHITE TYPE V WIDE WITH 6 ARM
72929	MLAR140LED50WUH	AREA LIGHT 140W LED 5000K WHITE WITH 6 ARM, 347/480V
73559	MLAR140LED50WUH/5W	AREA LIGHT 140W LED 5000K TYPE V WIDE WITH 6 ARM WHITE, 347/480V

Please contact your MaxLite representative to order products that don't have order codes listed here.